
ThermalCapture Fusion Zoom.

World's first fully aligned, super-lightweight zoom-able dual camera. For professional drone operations.









Of thermal +



Overlay

Thermal + Visual



Digital

Radiometric data



Visual Stabilized

Optical vibrationcompensation



Visual Zoom

10x times optical zoom



Geo-Referenced

Position + Time storage



Controllable

Remote via S-BUS / PWM

ThermalCapture Fusion Zoom is a dual camera (thermal & visual) especially designed for small drones. It stores full digital 14-bit radiometric thermal data as well as full digital visual data - both, completely aligned. With its lightweight design and 10x times (visual) optical zoom capability, it is the perfect and very flexible tool for unmanned operations within thermal mapping, security operations but also high level industrial inspections. Live view comes via analog video (PAL) and HDMI.





Dimensions: 83x71x46 mm 3.27x2.79x1.8 in


Weight: 310 gram 0.68 lb

Data output: SD card HDMI / AV (PAL)

Interfaces: MAVlink, NMEA, S-BUS, PWM

Housing: Carbon, Aluminum

Post-processing: ThermoViewer, FLIR Tools



Thermal sensor:

FLIR Tau 2 640 19mm Resolution 640 x 512 pixel

Thermal sensitivity:

0.05K (performance grade) or 0.03K (industrial grade)

Visual sensor:

TAMRON 1080p 10x zoom Resolution 1920 x 1080 pixel

